

Strategies to Meet Policy and Design Goals in City of Toronto


Learning Objectives

- 1. Understand how various components create green roof systems to achieve design intents**
- 2. Learn local policies aimed at enhancing sustainable development using green roofs**
- 3. Identify green roof systems that can successfully address a policy requirement**
- 4. Understand how a multi-disciplinary approach to designing green roofs is key**

80 years combined Green Roof experience



Technical advice,
design and planning



Budgetary estimates
and quotes



Certified installer
training



Single source
solutions – one stop
shop



Coordinate delivery of
all products to site



Supervise, inspect and
review final
installation



Warranty




NLSM Green Roof System Portfolio Overview

LiteN'Less® Classic II
 LiteN'Less® Classic III
 Xeroflor® XF301
 SpongeBase

StormCap®
 StormCap®+Detention
 TerraEXT®

Alpine Meadow
 Alpine Meadow +
 Roof Turf



Extensive
 \$170 – \$270 /m²
 (\$16 – \$25 /sf)

Semi-intensive
 \$210 – \$320 /m²
 (\$20 – \$30 /sf)

Intensive
 \$270 – \$650 /m²
 (\$25 – \$60 /sf)

Introduction to
Vegetated Roof Systems



Green Roof By-Law



TGS v4 W.Q. 1.1



TGS 4v W.Q. 1.3



Private residence, White Rock, BC

Toronto's Green Roof Bylaw



Gross Floor Area (Size of building)	Coverage of Available Roof Space (Size of Green Roof)
Residential/Commercial /Institutional	
2,000 - 4,999 m ²	20%
5,000 - 9,999 m ²	30%
10,000 - 14,999 m ²	40%
15,000 - 19,999 m ²	50%
20,000 m ² or greater	60%
Industrial	
>2,000m ²	Lesser of 10% or 2,000m ² or cool roof



LiteN'Less: Value Engineered Extensive System



Sedum Mat



Retention Fleece



Drainage/Filter




Root Barrier



Properties

Thickness	63 mm (2.5")
Saturated Weight	57 kg/m ² (11.7 lb/sf)
Water Retention	34 l/m ² (0.83 gal/sf)

Soiless System Installation





Water Retention Fleece

Soilless System Installation



Sherway Gardens North Expansion



Compliant with the Toronto Green Roof Construction Standard

TORONTO MUNICIPAL CODE
GREEN ROOFS

§ 492-9

E. Wind uplift.

The applicant shall provide a report, stamped by an engineer, providing wind uplift pressures being designed for (including a description of how the pressures were determined), and describing how the design addresses these pressures.

K. Vegetation performance.

In order to support plant survivability:

- (1) When structurally possible, the growing media shall be at a minimum 100 mm; or
- (2) The applicant shall provide a report confirming that the engineered system as designed provides plant survivability comparable to that of an un-irrigated system with growing media at minimum 100 mm.

Compliant with the Toronto Green Roof Construction Standard

Wind Resistance Letter



2 Queen Elizabeth Blvd.
Suite 102
Toronto, Ontario, M8Z 1L8
T. (416) 255-4447
LorEng@bellnet.ca

1. Xeroflor XF301 green roof system:

Green Roof Analysis Results:

The proposed green roof assembly for the above mentioned roof levels is XeroFlor XF301 system for which the composition is as follows:

- Xeroflor XF301 system green roof is based on a minimum dry weight of 0.17 kN/m²;
- XF 301 Sedum Mat, Combi (ST) on XF159 water retention fleece layer;
- XF108 XeroDrain drainage layer and 20 mil. XF112 root barrier;
- Approximate weight of total system as tested is 90.3 kg/m²;
- System installed over the prescribed roofing system.

The Xeroflor XF301 green roof system has been tested by the National Research Council of Canada in accordance with the CAN/CSA A123.24-15 "Standard Test Method for Wind Resistance of Modular Vegetated Roof Assembly" - Report No. A1-004442, dated Feb. 10, 2016. The report indicates a Wind Uplift Resistance of 6.4 kPa; and a Wind Flow Resistance of 113 km/hr. Report results are based on a safety factor of 1.5.

In comparing the aforementioned wind speed loading criteria with the reported factored wind flow capacity of the XeroFlor XF301 planting system, it is noted that the system is sufficient to resist anticipated wind flow forces which do not exceed speeds of 113km/hr and is adequate for use over the intended green roof areas.

The green roof system uplift resistance (6.4 kPa) is also noted to be sufficient to resist anticipated uplift forces and is adequate for use over the intended green roof areas. It should also be noted that Wind Uplift Resistance of the roofing system in accordance with CSA A123.21 will apply.

We trust this information is satisfactory for your requirements. Should you require additional information or clarification kindly contact the writer at your earliest convenience.

Thank you for your attention in these matters.

Best regards,

LorEng Construction Services Inc.

Per.: Loris Mogentale, P.Eng.
Ljm/LM



Plant Survivability Report

The XF301 extensive green roof system consists of 4 major components – a root barrier, a drainage/filter layer, a water retention layer and a pre-cultivated vegetation mat (Figure 1). It is designed, engineered and tested for long-term performance with low maintenance.

Weight of growing media: The saturated weight of the Xeroterr growing media within the XF301 Sedum Standard mat is 34 kg/m². The XF301 Sedum mat is composed of only 1.7cm of Xeroterr growing media (Figure 2). Calculation: 2000 kg/m³ ÷ 100 cm = 20 kg/cm/m² × 1.7cm = 34kg/m²

Figure 1 Principal components of the XF301 system



Figure 2 Sedum mat detail



The XF301 green roof system can be engineered to have different water retention capacity to meet the project requirements by incorporating different water retention layers in the build-up (Table 1). The water retention layers are made of lightweight, highly absorbent materials. They capture and store water effectively while keeping the weight of the green roof system low. The sedums grow and take up water and nutrients stored in the water retention layers.

Table 1 Comparison of XF301 pre-cultivated system to traditional plant-in-place system.


Green Roof System	Saturated Weight (kg/m ²)	Water Retention (L/m ²)
XF301 Standard Buildup	59	35.9
100 mm of Growing Medium	150	38.0

The XF301 Standard Build-up has similar water retention capacity as a green roof with 100 mm of growing medium. When un-irrigated, these systems capture and store similar amount of water for the plants to use and to tie the plants over until the next rainfall.

These succulents can survive with little water by nature but by adding a layer of stones as "mulch" to reduce water evaporation, even the XF301 pre-cultivated sedum mat and the XF301 Lightweight Buildup (with 17-26 L/m² water retention) can survive the hot and dry summer in the Greater Toronto Area (GTA).

The following pages show the plant growth and establishment of XF301 green roof systems with different water retention capacities over the years. All of these projects are un-irrigated. They are at least 5 years old and most of them are in the GTA. They are evidence of the long term plant survivability and success of un-irrigated XF301 green roof systems.

Performing the CSA A123.24 Wind Flow Test on NLSM's Soilless System



Air Flow Machine (front): specimen on test rig



Air Flow Machine (back): powerful twin fans

Wind Speed @ 200 km/h (124 mph)



Soilless System after passing 200 km/h: Minor leaf loss but otherwise unharmed



Before Test



After Test



WIND RESISTANCE TESTS
ON MODULAR VEGETATED ROOF ASSEMBLY
AS PER CSA A123.24

Prepared for: **Next Level Stormwater Management**
1, Yonge St. Ste 1801
Toronto, On, Canada
M5E 1W7


Attn: Ms. Sasha Aquilera

Report no.: AS-01419-B

Date: December 22th, 2020

Revision Date: January 11th, 2021

Prepared by: 
Justin Chagnon-Lafrance, Jr. Eng.
Project Manager, Materials and Systems Testing

Approved by: 
Jean Loubert, P.Eng.
Assistant Manager, Materials and Systems Testing

Test Results:

- Test stopped at 200 km/h (apparatus limit)
- After applying a generous safety factor of 1.5, the system's wind flow resistance is 133 km/h

Part B: Wind Flow Resistance

The wind flow resistance tests were performed by *UL Laboratory Canada Inc.*

The time elapsed between vegetated roof assembly construction (October 5th, 2020) and wind flow testing (October 6th, 2020) is 1 day.

Wind flow resistance: 133 km/h (83 mph)

Failure mode: No failure, test stopped at 200 km/h (124 mph) (Apparatus Limit)

Note: See Appendix B for Wind flow rating curve

To see a video on the full testing protocol, copy and paste this link into your browser:

<https://www.youtube.com/watch?v=uE5xz649ZxQ>

LABORATORY, FIELD TESTING AND ADVISORY SERVICES FOR THE BUILDING ENVELOPE
125 YEARS STRONG, UL LABORATORY CANADA INC. SERVING CUSTOMERS ACROSS NORTH AMERICA

CHICAGO US Headquarters 750 Anthony Trail Northbrook, IL 60062	MONTREAL Canada Headquarters 1320 Lionel-Boulet Blvd Verdun, QC J3K 1P7	QUEBEC 420 Charest East Blvd Suite 300 Quebec, QC G1K 8M4	OTTAWA 20 Capital Drive Suite 200 Ottawa, ON K2G 0E7	TORONTO 7 Underwriters Road Toronto, ON M1R 3A9	NEW YORK 747 Third Avenue 2nd Floor New York, NY 10017
--	---	---	--	---	--

T: 855.353.2532 W: ul.com/buildingenvelope E: buildingenvelope@ul.com

Unionville Condominiums
Markham, ON





Unionville Condominiums
Markham, ON

264

273

273

BioBerm: Enhancement with accent plants



Pre-vegetated Mat and/or Plant Plugs


Growing Medium

Retention Fleece

Drainage/Filter

Root Barrier

Roof Assembly



Properties

based on 15 cm (6") GM

Thickness	185 mm (7.3")
Saturated Weight	190 kg/m ² (38.9 psf)
Water Retention	68 l/m ² (1.7 gal/sf)

Introduction to
Vegetated Roof Systems



Green Roof By-Law



TGS v4 W.Q 1.1



TGS v4 W.Q 1.3





WATER QUALITY AND EFFICIENCY



Development
Feature

MANAGING STORMWATER

TIER 1

WQ 1.1 Water Balance, Quality Control & Quantity Control

Design the site to achieve all Water Balance, Water Quality and Water Quantity control targets required by the Wet Weather Flow Management Guidelines:

1) Water Balance- Retain a minimum of 50% of the total average annual rainfall volume (or equivalent 5 mm from each rainfall event) generated from all site surfaces through infiltration, evapotranspiration, water harvesting and/or reuse, in accordance with the Wet Weather Flow Management Guidelines.

2) Water Quality- Provide an enhanced level of protection for water quality through the long-term average removal of 80% of Total Suspended Solids (TSS) on an annual loading basis from all runoff leaving the site, in accordance with the Wet Weather Flow Management Guidelines. Provide E.coli control for direct discharges to Lake Ontario or for discharges generated from waterfront sites, where deemed necessary and in accordance with the Wet Weather Flow Management Guidelines.


3) Water Quantity- Provide peak flow control following applicable Wet Weather Flow Management Guideline requirements for flood flow management, erosion control and discharge to municipal sewers.





Rainfall

Initial Abstraction



Water Reuse

- Toilet flushing
- Irrigation

Initial Abstraction (IA)



Accounts for all losses prior to runoff and consists mainly of infiltration and evaporation

Surface Type	Initial Abstraction
Impervious Roof	1 mm
Asphalt Pavement	1 mm
Concrete Pavers	1 mm
Permeable Pavers	5 mm
Landscape	5 mm
Green Roof - Extensive	5 mm
Green Roof - Intensive	7 mm

impervious

pervious



Guild Inn, Toronto ON

Water Balance



Surface Type	Area (m ²)	Initial Abstraction (mm)	Volume Abstracted (m ³)	5 mm Volume (m ³)	Require Storage (m ³)
Impervious Roof	500	1	0.50		
Green Roof - Extensive	100	5	0.50		
Green Roof - Intensive	100	7	0.70		
Asphalt Pavement	200	1	0.20		
Landscape	100	5	0.50		
Total		2.4	2.4	5.0	2.6

Irrigation Water Reuse/Demand

Surface Type	Area (m ²)	Water Reuse (m ³)
Landscape	100	0.70
Green Roof - Extensive	100	0.70
Green Roof - Intensive	100	0.90
72-hour average		2.3



Storage Volume

Storage Volume > **Water Reuse** ❌

Water Reuse

Water Balance

Surface Type	Area (m ²)	Initial Abstraction (mm)	Volume Abstracted (m ³)	5 mm Volume (m ³)	Required Storage (m ³)
Impervious Roof	470	1	0.47		
Green Roof - Extensive	130	5	0.65		
Green Roof - Intensive	100	7	0.70		
Asphalt Pavement	200	1	0.20		
Landscape	100	5	0.50		
Total		2.5	2.5	5.0	2.5



Irrigation Water Reuse/Demand

Surface Type	Area (m ²)	Water Reuse (m ³)
Landscape	100	0.70
Green Roof - Extensive	130	0.93
Green Roof - Intensive	100	0.90
72-hour average		2.5



Storage Volume

Water Reuse

Storage Volume

≤

Water Reuse



Water Balance - Irrigation Water Reuse/Demand

$$WR = \frac{(ET_0 * K_L - R_e) * A}{IE}$$

equation 1



where

WR = Water Requirement/Demand (l/month)

ET_0 = Local Reference Evapotranspiration (mm/month)

K_L = Landscape Coefficient (dimensionless)

R_e = Effective Rainfall (mm/month), defined as 25% of average peak monthly rainfall

A = Area (m^2)

IE = Irrigation Efficiency (dimensionless)

Irrigation Water Reuse – Landscape Coefficient



$$K_L = K_S * K_D * K_{MC} \quad \text{equation 2}$$

where

K_L = Landscape Coefficient (dimensionless)

K_S = Species Factor (dimensionless)

K_D = Density Factor (dimensionless)

K_{MC} = Microclimate Factor (dimensionless)

Water Needs	K_S
Very low	<0.1
Low	0.1 - 0.3
Moderate	0.4 - 0.6
High	0.7 - 0.9

Density	K_D
Low	0.5 - 0.9
Average	1
High	1.1 - 1.3

Water Needs	K_{MC}
Low	0.5 - 0.9
Average	1
High	1.1 - 1.4

Tips to support the Civil engineer in meeting W.Q1.1 water balance requirements

- Ensure the landscape and green roof areas listed on the water balance table are accurate.
- Ensure the green roof area is listed under the appropriate category on the water balance table. Ex. Extensive GR = 5 mm IA, Intensive GR = 7 mm IA.
- Recommend irrigation as a means of water re-use where appropriate.
- Convert amenity space landscape into “Intensive Green Roofs” for an extra 2 mm IA.

Introduction to
Vegetated Roof Systems



Green Roof By-Law



TGS v4 W.Q 1.1



TGS v4 W.Q 1.3



Golf Park Maisonneuve, Montreal, QC



WATER QUALITY AND EFFICIENCY



Development
Feature

MANAGING STORMWATER

TIER 1

WQ 1.3 On-site Green Infrastructure

Ensure that the total landscaped site area, located at and above grade, includes at least one of the following features:


- A Green Roof covering at least 80% of Available Roof Space;
- An Intensive Green Roof for 80% of the Green Roof Area provided;
- Biodiverse green roof to support pollinator species covering a minimum of 50% Green Roof Area;
- 25% of the Lot Area at or above-grade, planted with native flowering/pollinator species;
- At-grade Bioretention facilities provided to capture and control 75% of runoff from on-site hardscape surfaces; or,
- Reforestation of a portion of the site (beyond the limit of a stewardship plan).



TGS WQ 1.3: Option 1 - 80% Green Roof Cover

A green roof covering at least 80% of the Available Roof Space

Extensive or Intensive Systems



TGS WQ 1.3: Option 1 - 80% Green Roof Cover

A green roof covering at least 80% of the Available Roof Space



TGS WQ 1.3: Option 2 - Intensive Green Roof

An intensive green roof for 80% of the green roof area provided



TGS V4
(e.g. 80% of green
roof area provided)

Available Roof Space

- Deeper substrates that can support a greater variety of plant species.
- Minimum depth of 150 mm
- A diverse mix of plants
- Plants may include sedums. Grasses, drought tolerant perennials. And larger plants and trees where appropriate.

TGS WQ 1.3: Option 3 - Biodiverse Green Roof

Biodiverse green roof to support pollinator species covering a minimum of 50% of the green roof area provided



TGS V4
(e.g. 50% of green
roof area provided)

Green Roof
Bylaw (e.g. 60%)

Available Roof Space

- An intensive green roof
- Support pollinator species from [Design Guidelines for Biodiverse Green Roofs – Appendix A](#)
- Min. two pollinator species in bloom from May – Sep.
- Two or more applicable Design Strategies from section 4.2 of the Guidelines.
- Located on the 8th floor or lower

Alpine Meadow



Meadow Blanket



Growing Medium



Filter Fabric

Edging

Drainage Mat

Root Barrier

Conventional Roofing Assembly (CRA)

Key Features

- Manages stormwater and supports biodiversity, simultaneously. Native hardy plants provide nourishing pollen and nectar, and nesting habitats
- Plants are pre-grown as a "blanket" with over 85% vegetation coverage upon installation; minimizing soil erosion, weed encroachment and irrigation needs.

Green Roof Options to Meet TGS WQ 1.3

TGS WQ 1.3 Green Roof Options	Compliance Requirements	NLSM Solutions
A Green Roof covering at least 80% of Available Roof Space	<ul style="list-style-type: none"> Any green roof covering at least 80% of Available Roof Space 	<ul style="list-style-type: none"> LiteN'Less Classic II / III XF301 / XF300 StormCap TerraEXT FloraEXT
An Intensive Green Roof for 80% of the Green Roof Area provided	<ul style="list-style-type: none"> Minimum growing medium depth of 150 mm Diverse plant mix including sedum, grasses, perennials and trees 	<ul style="list-style-type: none"> Eco-Grass Flora Garden
Biodiverse green roof to support pollinator species covering a minimum of 50% Green Roof Area	<ul style="list-style-type: none"> An intensive green roof Support pollinator species from Design Guidelines for Biodiverse Green Roofs – Appendix A Minimum two pollinators species in bloom from May to Sep Two or more applicable Design Strategies from Section 4.2 of the Design Guidelines above Located on 8th floor or lower 	<ul style="list-style-type: none"> Alpine Meadow Alpine Meadow+

Meeting Requirements with Green Roofs

Requires coordinated efforts of a multi-disciplinary team



Engineer (Civil & Mechanical):
water balance calculations



Architect:
site surface types/areas



Landscape Architect:
landscape plan



Irrigation consultant:
Irrigation demand



Developer:
Costing



Green roof supplier:
System buildup

Common Pitfalls

Water Access Hose bibs or irrigations systems



Sherway Gardens
Toronto ON Canada



Access Points



Designated Access Paths and Vegetation- Free Zones

Blythwood at Huntington
Toronto ON Canada



Sherway Gardens
Toronto ON



Fall Arrest Anchors



Blywood Condo
Toronto ON Canada



At installation

Damage by Foot Traffic



1 year later

Uptown Towers
Toronto ON Canada




Canopies

Regent Park
Toronto ON Canada



Landscape drawings to include:

- A reference dimension right on the landscape drawing
- Gridlines to compare and contrast against architectural plans, sections & elevations
- Architectural details such as skylights, equipment, walkways, drains, anchors...etc.



PV Integration


Stormwater Management

Amenity Space

Lightweight & Economical

Energy Saving

Enhanced Biodiversity



Water Quality & Efficiency WQ 1.3 On-site Green Infrastructure - Mid-high Rise Residential & Non-Residential

Ensure that the total landscaped site area, located at and above grade, includes at least one of the 6 features below:

	Feature Description	Min. 150 mm GM	located on ≤ 8 stories	Plant List Type	Bloom requirement	Design Strategy	5 Yr. Mtnc. Program	Permanent Irrigation System	Mtnc. access
1	A Green Roof covering at least 80% of Available Roof Space; ⁴								
2	An Intensive Green Roof for 80% of the Green Roof Area provided; ^{5,7}	Required		Diverse mix*			Required	Required	Door or hatch
3	Biodiverse green roof to support pollinator species covering a minimum of 50% Green Roof Area; ^{6,7}	Required	Required	Appendix A [†]	Two at all times from May to Sep	Two Required ⁵	Required	Required	Door or hatch
4	25% of the Lot Area at or above-grade, planted with native flowering/pollinator species; ⁸								
5	At-grade Bioretention facilities provided to capture and control 75% of runoff from on-site hardscape surfaces; or, ⁹								
6	Reforestation of a portion of the site (beyond the limit of a stewardship plan). ¹⁰								